



POE+
Power supply centralization
for simplifying your solution

KEY PERFORMANCE
Gigabit Ethernet ports for
high-bandwidth data throughput



INDUSTRIAL DESIGN
Compact, sturdy, and easy to install –
perfect for industrial applications



POE+ SWITCHES

TSW100 // TSW101 // TSW200



TSW100

INDUSTRIAL UNMANAGED POE+ SWITCH

Powering option
4-pin power socket, 7-57 VDC (input
voltage range for PoE 44-57 VDC)

**PoE standart & Total PoE power
budget (at PSE)**
802.3af and 802.3at, 120 W

Ethernet
5 x RJ45 ports, 10/100/1000 Mbps:
4 x PoE, 1 x Uplink

Bandwidth (non-blocking)
10 Gbps

Housing & mounting
Aluminium housing with DIN rail
mounting option

Measurements & weight
115 x 32 x 95 mm, 350 g



TSW101

AUTOMOTIVE POE+ SWITCH

Powering option
2-pin power DC socket, 9-30 VDC
(input voltage range for
PoE 9-30 VDC)

**PoE standart & Total PoE power
budget (at PSE)**
802.3af and 802.3at, 60 W

Ethernet
5 x RJ45 ports, 10/100/1000 Mbps:
4 x PoE, 1 x Uplink

Bandwidth (non-blocking)
10 Gbps

Housing & mounting
Aluminium housing with DIN rail
mounting option

Measurements & weight
115 x 32 x 95 mm, 384 g



TSW200

INDUSTRIAL UNMANAGED POE+ SWITCH

Powering option
2-pin power socket, 7-57 VDC (input
voltage range for PoE 44-57 VDC)

**PoE standart & Total PoE power
budget (at PSE)**
802.3af and 802.3at, 240 W

Ethernet
8 x RJ45 ports, 10/100/1000 Mbps

Bandwidth (non-blocking)
20 Gbps

Interfaces
2 x SFP

Housing & mounting
Aluminium housing; Integrated DIN
rail bracket (on a standart order
code)

Measurements & weight
132 x 44.2 x 95.1 mm, 517 g

FULL CONTROL

Manage your entire network's infrastructure

VERSATILITY

Gigabit Ethernet, SFP, PoE+, and more

PROFINET SUPPORT

Supports Profinet & other key communication protocols



MANAGED SWITCHES

TSW202 // TSW212



TSW202

MANAGED PoE+ SWITCH

Powering option

2-pin power socket, 7-57 VDC (input voltage range for PoE 44-57 VDC)

PoE standart & Total PoE power budget (at PSE)

802.3af and 802.3at, 240 W

Ethernet

8 x RJ45 ports, 10/100/1000 Mbps

Bandwidth (non-blocking)

20 Gbps

Interfaces

2 x SFP

Housing & mounting

Anodized aluminum housing and panels; Integrated DIN rail bracket (on a standart order code)

Measurements & weight

132 x 44.2 x 122.2 mm, 610 g



TSW212

MANAGED NETWORK SWITCH

Powering option

2-pin power socket, 7-57 VDC

Ethernet

8 x RJ45 ports, 10/100/1000 Mbps

Bandwidth (non-blocking)

20 Gbps

Interfaces

2 x SFP

Housing & mounting

Anodized aluminum housing and panels; Integrated DIN rail bracket (on a standart order code)

Measurements & weight

132 x 44.2 x 122.2 mm, 615 g

INDUSTRIAL-GRADE

Sturdy aluminium housing resistant to vibrations and extreme temperatures

PLUG N PLAY

No additional configuration needed, no time wasted

ADAPTABLE

Wide voltage range and DIN rail mounting



ETHERNET SWITCHES

TSW110 // TSW210 // TSW010 // TSW114 // TSW304



TSW110

L2 UNMANAGED SWITCH

Powering option

4-pin power socket, 9 - 30 VDC

Ethernet

5 x RJ45 ports, 10/100/1000 Mbps

Bandwidth (non-blocking)

10 Gbps

Housing & mounting

Aluminium housing with DIN rail mounting option

Measurements & weight

100 x 30 x 85 mm, 227 g



TSW210

UNMANAGED INDUSTRIAL SWITCH

Powering option

2-pin power socket, 7-57 VDC

Ethernet

8 x RJ45 ports, 10/100/1000 Mbps

Bandwidth (non-blocking)

20 Gbps

Interfaces

2 x SFP

Housing & mounting

Aluminium housing; Integrated DIN rail bracket (on a standart order code)

Measurements & weight

132 x 44.2 x 95.1 mm, 500 g

SWITCHES



TSW010

DIN RAIL SWITCH

Powering option

2-pin power DC socket, 9 - 30 VDC

Ethernet

5 x RJ45 ports, 10/100 Mbps

Bandwidth (non-blocking)

1 Gbps

Housing & mounting

Anodized aluminium housing and panels; Integrated DIN rail bracket

Measurements & weight

113.1 x 27.4 x 80.5 mm, 146.5 g



TSW114

DIN RAIL SWITCH

Powering option

2-pin power DC socket, 9 - 30 VDC

Ethernet

5 x RJ45 ports, 10/100/1000 Mbps

Bandwidth (non-blocking)

10 Gbps

Housing & mounting

Anodized aluminium housing and panels; Integrated DIN rail bracket

Measurements & weight

113.1 x 27.4 x 80.5 mm, 174 g



TSW304

DIN RAIL SWITCH

Powering option

2-pin power DC socket, 7 - 57 VDC /
9 - 40 VAC

Ethernet

4 x RJ45 ports, 10/100/1000 Mbps

Bandwidth (non-blocking)

8 Gbps

Housing & mounting

Anodized aluminium housing and panels; Integrated DIN rail bracket

Measurements & weight

102 x 25 x 81.5 mm, 210 g

FROM ENGINEERS, TO ENGINEERS

Our hardware engineering is rooted in simplicity and precision, and our devices are built with engineer needs in mind – balancing performance, functionality, and durability. This ensures that our products don't only meet industry requirements, but continue to excel long into the future.

HEAD OF HARDWARE

LUKAS ŽAROVAS